

# InteliVision 5 CAN

REMOTE COLOR DISPLAY UNIT WITH CAN BUS INTERFACE



Lloyd's  
Register

The IV-5 remote display is a new generation display unit equipped with a galvanically isolated CAN interface to improve the reliability of data communication from the master controller. Active backlit buttons improve usability and ensure operators can access important data quickly.

The IV-5 is designed as a fully IP65 waterproof unit, 'Plug & Play' solution and displays all genset data and monitoring information in a highly visible, colorful and forward looking screen design.

- ▶ 5.7" color TFT display
- ▶ Overall size 9.7 x 6.5" (247 x 165 mm)
- ▶ Panel cutout 6.7 x 4.3" (170 x 110 mm)
- ▶ Depth behind panel 1.3" (33 mm)
- ▶ Works with IntelliDrive DCU and IntelliGen<sup>NT</sup> Marine controllers
- ▶ Factory-configured and tested with associated controller and genset
- ▶ Analog input for backlight dimming
- ▶ Binary output for alarm horn
- ▶ Maximum 650' (200 m) cable length to local panel



**NORTHERN LIGHTS**  
[www.northern-lights.com](http://www.northern-lights.com)

Northern Lights, Inc. • 4420 14th Ave. NW, • Seattle WA 98107  
Tel: 206-789-3880 • 1-800-762-0165 • Fax: 206-782-5455 • [www.northern-lights.com](http://www.northern-lights.com)  
Northern Lights, Inc. © 2015 All rights reserved. 8/15 L792