



- High capacity accumulator-drier
- Electrical components housed in non-conductive Bakelite enclosure
- Wire covered in fire resistant sheathing
- Fluted copper-nickel and copper jacketed condenser for maximum efficiency
- Stainless steel vibration isolation mounting

SPECIFICATIONS AND DIMENSIONS

Model	BTU @ 60 HZ (50 HZ)	AMP Draw 115V (230V)	Dimensions: HxWxD in. (mm)	Weight: Lbs (kg)
RC08	8,000 (6,600)	8.9 (4.4)	14 (355.6) x 10 (254) x 14 (355.6)	59 (26.79)
RC12	12,000 (10,000)	n/a (5.9)	14 (355.6) x 10 (254) x 14 (355.6)	64 (29.06)
RC16	16,000 (13,250)	15 (6.2)	14 (355.6) x 10 (254) x 14 (355.6)	66 (29.96)
RC24	24,000 (20,000)	n/a (12)	17 (431.8) x 15.25 (387.3) x 26.5 (673.1)	120 (54.48)
RC32	32,000 (26,500)	n/a (16.5)	17 (431.8) x 15.25 (387.3) x 26.5 (673.1)	128 (58.11)
RC40	40,000 (33,000)	n/a (22.5)	17 (431.8) x 15.25 (387.3) x 26.5 (673.1)	130 (59.02)
RC48	48,000 (40,000)	n/a (22.7)	16.8 (426.7) x 15.75 (400) x 26.5 (673.1)	149 (67.65)
RC60	60,000 (50,000)	n/a (26)	18.71 (475.2) x 15.75 (400) x 26.5 (673.1)	152 (69.01)

Information and dimensions are subject to change without notice.

FEATURES AND BENEFITS

- » Single pass fluted coaxial copper-nickel counter flow condenser allows low sea water velocity while providing maximum efficiency and even condensing.
- » High and low charging ports easily accessible.
- » Wiring covered with fire resistant sheathing.
- » 316L grade stainless steel chassis, fasteners and hardware.
- » Rubber vibration compressor isolation mounting feet.
- » Small overall size.
- » Two-part urethane paint system.

DIMENSIONAL DRAWINGS

