



SPECIFICATIONS AND DIMENSIONS

Model	BTU @ 60 HZ	BTU @ 50 HZ	AMP Draw (230V 1ph)	CFM	Dimensions: HxWxD in. (mm)	Weight: Lbs (kg)
RAVC12	12,000	10,000	0.62	370	25.8 (655) x 20.5 (520) x 8.7 (221)	36.5 (16.6)
RAVC16	16,000	13,200	0.78	450	25.8 (655) x 20.5 (520) x 8.6 (218)	38.2 (17.3)
RAVC18	18,000	15,000	0.78	450	25.8 (655) x 20.5 (520) x 7.125 (181)	43.5 (19.7)

Specifications may change without notice.

Dimensions represent the blower in a vertical discharge position without a duct ring or plenum box attached.

Dimensions shown without electrical heat options.

FEATURES AND BENEFITS

- » Space saving design with minimal foot print for tight installations.
- » Constructed with 16 gauge 316L grade stainless steel shroud, and insulated pan with twin drains.
- » Fully insulated stainless steel plenum.
- » Two inch deep insulated stainless steel pans contain condensate.
- » Bleeder hose and valve come standard.
- » Fully rated fan coil set.
- » High velocity, rotatable insulated blowers.
- » Custom water valve locations available.
- » Heat strips and UV lamp options available.
- » Engineered to eliminate the need for vibration isolation mounts.
- » Designed to thrive in harsh marine environments.

DIMENSIONAL DRAWINGS

