



SPECIFICATIONS AND DIMENSIONS

Model	BTU @ 60 HZ (50 HZ)	AMP Draw 115V 1ph (230V)	CFM	Dimensions: HxWxD in. (mm)	Weight: Lbs (kg)
RE08	8,000 (6,600)	1.86 (0.93)	265	9.5 (241) x 14.1 (358.1) x 13.79 (350.2)	19 (8.62)
RE12	12,000 (10,000)	3.20 (1.60)	350	12.25 (311) x 15.5 (393.7) x 16.82 (427.2)	25 (11.35)
RE16	16,000 (13,250)	3.55 (1.70)	500	12.25 (311) x 15.5 (393.7) x 17.3 (439.4)	27 (12.26)
RE24 TXV	24,000 (20,000)	6.40 (3.20)	700	12.25 (311) x 32 (813) x 15.8 (401.3)	51 (23.13)
RE32 TXV	32,000 (26,500)	7.10 (3.40)	1,000	12.25 (311) x 32 (813) x 17.45 (443.2)	55 (24.95)

Specifications may change without notice.

Dimensions represent the blower in a vertical discharge position without a duct ring or plenum box attached.

Dimensions shown without electrical heat options.

FEATURES AND BENEFITS

- » Constructed with 16 gauge 316L grade stainless steel shroud and insulated pan with two drains.
- » 2 inch deep pans contain condensation.
- » Fully rated fan coil set.
- » Insulated, rotatable multi-position blowers with cap tube and electric heat.
- » 24,000 and 32,000 BTU units feature thermostatic expansion valve (TXV) and dual blower arrangement for ease of installation.
- » Engineered to eliminate the need for vibration isolation mounts.
- » Designed to withstand harsh marine environments.
- » All models available with optional electric heat strips and UV light.

DIMENSIONAL DRAWINGS

