



## SPECIFICATIONS AND DIMENSIONS

| Model  | BTU @ 60 HZ (50 HZ) | AMP Draw 115V (230V) | Heat Amps (kW) | CFM   | Dimensions: HxWxD in. (mm)           | Weight: Lbs (kg) |
|--------|---------------------|----------------------|----------------|-------|--------------------------------------|------------------|
| RA12VB | 12,000 (10,000)     | 0.56                 | 8.7 (2)        | 350   | 12.8 (325) x 18.5 (470) x 12.9 (329) | 28 (12.70)       |
| RA16VB | 16,000 (13,200)     | 0.56                 | 8.7 (2)        | 500   | 12.2 (311) x 18.5 (470) x 12.6 (319) | 28.7 (13.02)     |
| RA18VB | 18,000 (15,000)     | 0.56                 | 8.7 (2)        | 500   | 12.3 (314) x 19.9 (505) x 13.4 (340) | 33.7 (15.29)     |
| RA24VB | 24,000 (20,000)     | 0.56                 | 10.8 (2.5)     | 700   | 13.1 (333) x 35.0 (889) x 13.1 (332) | 53 (24.04)       |
| RA32VB | 32,000 (26,500)     | 0.56                 | 10.8 (2.5)     | 1,000 | 12.8 (324) x 35.0 (889) x 12.7 (323) | 56.4 (25.6)      |

Specifications may change without notice.

Dimensions represent the blower in a vertical discharge position without a duct ring or plenum box attached.

Dimensions shown without electrical heat options.

## FEATURES AND BENEFITS

- » Constructed with 16 gauge 316L grade stainless steel shroud and insulated pan with two drains.
- » 2 inch deep pans contain condensation.
- » Standard with bleeder hose and valve.
- » Fully rated fan coil set.
- » Rotatable insulated blowers.
- » 24,000 and 32,000 BTU units feature dual blower arrangement for ease of installation.
- » Engineered to eliminate the need for vibration isolation mounts.
- » Designed to withstand harsh marine environments.
- » All models available with optional electric heat strips and UV light.

## DIMENSIONAL DRAWINGS

