



SPECIFICATIONS AND DIMENSIONS

Model	BTU @ 60 HZ (50 HZ)	AMP Draw 115V (230V)	Dimensions: HxWxD in. (mm)	Weight: Lbs (kg)
RA08	8,000 (6,600)	1.86 (0.93)	9 (228.6) x 16.8 (426.7) x 13.8 (350.5)	59 (26.79)
RA12	12,000 (10,000)	3.20 (1.60)	12.25 (311.1) x 18.5 (469.9) x 15.75 (400)	64 (29.06)
RA16	16,000 (13,250)	3.55 (1.70)	12.25 (311.1) x 18.5 (469.9) x 17.3 (439.4)	66 (29.96)
RA18	18,000 (15,000)	3.55 (1.70)	12 (304.8) x 19 (482.6) x 18.25 (463.5)	28 (21.71)
RA24	24,000 (20,000)	6.40 (3.20)	12.25 (311.1) x 35 (889) x 15.8 (401.3)	120 (54.48)
RA32	32,000 (26,500)	7.10 (3.40)	12.25 (311.1) x 35 (889) x 17.5 (439.4)	128 (58.11)

Information and dimensions are subject to change without notice.

FEATURES AND BENEFITS

- » Constructed with 16 gauge 316L grade stainless steel shroud and insulated pan with two drains.
- » 2 inch deep stainless steel drip pans contain condensation.
- » Standard with bleeder hose and valve.
- » Fully rated fan coil set.
- » High-volume, rotatable blower, insulated for quiet operation.
- » 24,000 and 32,000 BTU units feature dual blower arrangement for ease of installation.
- » Engineered to eliminate the need for vibration isolation mounts.
- » Designed to withstand harsh marine environments.
- » All models available with optional electric heat strips and antimicrobial UV light.

DIMENSIONAL DRAWINGS

