



### SPECIFICATIONS AND DIMENSIONS

Model	BTU @ 60 HZ (50 HZ)	AMP Draw 115V (230V)	Heat Amps (kW)	CFM	Dimensions: HxWxD in. (mm)	Weight: Lbs (kg)
RA12VB	12,000 (10,000)	0.56	8.7 (2)	350	12.8 (325) x 18.5 (470) x 12.9 (329)	28 (12.70)
RA16VB	16,000 (13,200)	0.56	8.7 (2)	500	12.2 (311) x 18.5 (470) x 12.6 (319)	28.7 (13.02)
RA18VB	18,000 (15,000)	0.56	8.7 (2)	500	12.3 (314) x 19.9 (505) x 13.4 (340)	33.7 (15.29)
RA24VB	24,000 (20,000)	0.56	10.8 (2.5)	700	13.1 (333) x 35.0 (889) x 13.1 (332)	53 (24.04)
RA32VB	32,000 (26,500)	0.56	10.8 (2.5)	1,000	12.8 (324) x 35.0 (889) x 12.7 (323)	56.4 (25.6)

Specifications may change without notice.

Dimensions represent the blower in a vertical discharge position without a duct ring or plenum box attached.

Dimensions shown without electrical heat options.

### FEATURES AND BENEFITS

- » Constructed with 16 gauge 316L grade stainless steel shroud and insulated pan with two drains.
- » 2 inch deep pans contain condensation.
- » Standard with bleeder hose and valve.
- » Fully rated fan coil set.
- » Rotatable insulated blowers.
- » 24,000 and 32,000 BTU units feature dual blower arrangement for ease of installation.
- » Engineered to eliminate the need for vibration isolation mounts.
- » Designed to withstand harsh marine environments.
- » All models available with optional electric heat strips and UV light.

### DIMENSIONAL DRAWINGS

