



### SPECIFICATIONS AND DIMENSIONS

Model	BTU @ 60 HZ (50 HZ)	AMP Draw (230V)	Heat Amps (kW)	CFM	Dimensions: HxWxD in. (mm)	Weight: lbs (kg)
RA08	8,000 (6,600)	0.89	3 (.75)	297	9.6 (244) x 17.8 (453) x 14.4 (365)	23.5 (10.65)
RA12	12,000 (10,000)	0.56	8.7 (2)	350	12.8 (325) x 19.5 (494) x 15 (382)	28 (12.7)
RA16	16,000 (13,200)	0.56	8.7 (2)	500	12.8 (325) x 19.5 (494) x 14.6 (370)	33.7 (15.29)
RA18	18,000 (15,000)	0.56	8.7 (2)	500	12.8 (325) x 20 (509) x 15.98 (406)	40 (18.14)
RA24	24,000 (20,000)	2 x 0.56	10.8 (2.5)	700	13.1 (333) x 35 (889) x 13.1 (332)	53 (24)
RA24S	24,000 (20,000)	1.55	10.8 (2.5)	825	15.1 (384) x 22.7 (576) x 16.7 (425)	47 (21.31)
RA32	32,000 (26,500)	2 x 0.56	10.8 (2.5)	1,000	12.8 (324) x 35 (889) x 12.7 (323)	56.4 (25.6)

- Specifications may change without notice.
- Dimensions represent the blower in a vertical discharge position without a duct ring or plenum box attached.
- Dimensions shown do not change with added electric heat or uv options.
- Consult Factory for 115 volt models.

### FEATURES AND BENEFITS

- » Constructed with 16 gauge 316L grade stainless steel shroud and insulated pan with two drains.
- » 2 inch deep pans contain condensation.
- » Standard with bleeder hose and valve.
- » Fully rated fan coil set.
- » Rotatable insulated blowers.
- » RA24 and RA32 units feature dual blower arrangement. RA24S features a single blower.
- » Engineered to eliminate the need for vibration isolation mounts.
- » Designed to withstand harsh marine environments.
- » All models available with optional electric heat strips and UV light.

### DIMENSIONAL DRAWINGS

