

AC Output

36 kW	60 Hz, 1800 RPM, 3 Ph, 0.8 PF, 120-208V / 125A, 120V / 300A
Optional	Single Phase with 1.0 PF
Voltage regulation	± 1%

Lugger L944 Engine

Type	Vertical inline 4 cylinder diesel
Displacement	203 cubic in (3.33 ltr)
Bore/Stroke	3.70/4.72 in (94/120 mm)
Aspiration	Turbocharged
Fuel System	Bosch type inline injection pump

Approx. fuel use

1800 RPM @ full load ²	3.3 gph (12.3 lph)
1800 RPM @ half load ²	1.6 gph (6.0 lph)


Installation Data & Weight

Fuel inlet and return	1/4 inch NPT
Approximate dry weight	1390 lbs (630 kg)

1. Deratings: 3% per 1000 ft. over 500 feet above sea level.
1.5% for every 10° over 77°F

2. Actual fuel consumption will vary depending on operating conditions

DIMENSIONAL DRAWING



NL944T3 Overall Dimensions L x W x H: 64.8 x 25.6 x 35.8 in (1647 x 650 x 910 mm)

Dimensions given in inches (mm). Dimensions subject to change without notice.
Contact dealer or visit www.northern-lights.com for most current installation drawings.

NL944T3 FEATURES AND BENEFITS

ENGINE BLOCK

- Lugger, four cycle, 4 cylinder, liquid cooled, turbocharged, overhead valve industrial duty diesel engine.
- Two valves per cylinder.
- Double wall oil pan.
- Crankshaft is induction hardened, forged carbon steel; stronger than cast iron.
- Helical cut and ground carbon steel timing gears reduce noise.
- Cross flow head for efficient breathing.

COOLING SYSTEM

- Liquid cooled with radiator and pusher cooling fan. Radiator shroud and fan hand guard.

FUEL SYSTEM

- Direct injection with glow plugs.
- Bosch-type in-line injection pump with 5% mechanical governor for close AC output frequency control.
- Pintle type injectors.
- Mechanical fuel lift pump with hand primer.
- Large spin-on fuel filter.
- Flexible fuel lines routed to base.
- Stop solenoid controls fuel rack, not throttle, for fast engine shutdowns.

INTAKE AND EXHAUST

- Meets US EPA interim Tier IV emission requirements.
- Large air cleaner with replaceable filter element.

LUBRICATION SYSTEM

- Full flow, spin-on oil filter.

DC ELECTRICAL SYSTEM

- DC system uses reliable relays instead of unrepairable printed circuit board.
- 12 volt starter and battery charging alternator with regulator.
- Standard panel: J-box mounted S-1B has hour meter, shutdown bypass, stop-start switch and preheat switch.
- Low oil pressure and high coolant temperature shutdowns are standard.

AC GENERATOR

- Northern Lights, direct coupled, 4-pole, revolving field generator with Class H insulation, and pre-lubricated, double sealed bearing. Brushless design is maintenance free.
- 12 lead, 3 phase standard.
- Conservative temperature rise rating of 105°C/ 40°C, ideal for applications in extreme climates and continuous operation.
- Automatic Voltage Regulator (AVR) gives quick +/-1% RMS no load to full load voltage regulation.
- High air flow from cast aluminum fan keeps generator running cool.
- Terminal strip in j-box for easy voltage changes and connection to AC distribution system.

SPECIAL EQUIPMENT

- Steel base frame provides rigid support and makes installation easy.
- Vibration mounts isolate engine vibration for smooth, quiet operation.
- Long life, Imron® enamel finish for excellent service visibility.
- Operator's and parts manuals standard. Optionally available on CD-ROM.
- Each set is test run on load bank.

NOTE: Tier III Standby Emergency Duty Only